



EARTH LEAKAGES, AUXILIARY, SHUNT TRIP & ISOLATORS - DIN MOUNT



* Voltage Rating : 230V / 400V 50-60 Hz • Insulation Voltage Ui : 500V • Electric Life : ≥ 4000 • Mechanical Life : ≥ 10 000 • SABS in Accordance to: IEC 60947-2 Standards



NH2-100 132
ISOLATOR (1 POLE)

ISOLATORS - DIN MOUNT *

Part Number	Unit Width (mm)	No of Poles	Current Rating	UNIT PRICE (excl. VAT)
NH2-100 132	18mm	1 Pole	32 Amp	R 79.00
NH2-100 163	18mm	1 Pole	63 Amp	R 92.00
NH2-100 1100	18mm	1 Pole	100 Amp	R 118.00
NH2-100 232	36mm	2 Pole	32 Amp	R 99.00
NH2-100 263	36mm	2 Pole	63 Amp	R 132.00
NH2-100 2100	36mm	2 Pole	100 Amp	R 217.00
NH2-100 332	54mm	3 Pole	32 Amp	R 164.00
NH2-100 363	54mm	3 Pole	63 Amp	R 211.00
NH2-100 3100	54mm	3 Pole	100 Amp	R 224.00
NH2-100 432	72mm	4 Pole	32 Amp	R 211.00
NH2-100 463	72mm	4 Pole	63 Amp	R 237.00
NH2-100 4100	72mm	4 Pole	100 Amp	R 250.00

EARTH LEAKAGE PROTECTION - DIN MOUNT

Part Number	Ka Rating	No of Poles	Current Rating	UNIT PRICE (excl. VAT)
NL1-63 125	30mA	1 Pole + N	25 Amp	R 322.00
NL1-63 140	30mA	1 Pole + N	40 Amp	R 322.00
NL1-63 163	30mA	1 Pole + N	63 Amp	R 322.00
NL1-63 325	30mA	3 Pole + N	25 Amp	R 633.00
NL1-63 340	30mA	3 Pole + N	40 Amp	R 646.00
NL1-63 363	30mA	3 Pole + N	63 Amp	R 660.00



NL1-63 125
MINI EARTH LEAKAGE UNIT

SIDE MOUNT AUXILIARY FOR NB1 RANGE

Part Number	Description	Auxiliary Contact	UNIT PRICE (excl. VAT)
NB1-XF9	Side Mount Auxiliary	1 NO + 1 NC	R 178.00

SIDE MOUNT SHUNT TRIP FOR NB1 RANGE

Part Number	Description	Coil Voltage	UNIT PRICE (excl. VAT)
NB1-S9-M	Clip-on Shunt Trip	230 Volt	R 224.00
NB1-S9-Q	Clip-on Shunt Trip	400 Volt	R 224.00

PADLOCK DEVICE FOR NB1 RANGE

Part Number	Description	UNIT PRICE (excl. VAT)
NB1-LOCK	Toggle mounting device for pad-lock for single to triple poles	R 19.00

UNDER VOLTAGE RELEASE FOR NB RANGE

Part Number	Description	UNIT PRICE (excl. VAT)
NB1-UVT	Under Voltage Release for NB1, NBH8, NB1L, NB3LE, NBH8LE Ranges	P.O.A