

## AC Miniature Contactor (NC6)

Code	NC6-0610	NC6-0601	NC6-0910	NC6-0901
Frame Size	11,5A	11,5A	11,5A	11,5A
AC1 Rating	20A	20A	20A	20A
AC3 Rating (220/240V)	1.5kW / 7A	1.5kW / 7A	1.5kW / 7A	1.5kW / 7A
AC3 Rating (380/440V)	2.2kW / 6A	2.2kW / 6A	4kW / 9A	4kW / 9A
Auxillary Contacts	1NO	1NC	1NO	1NC
AC Coil Voltages	AC			
Voltages	110V, 240V, 415V			
Dimintions (AC)	45mm (w) x 58mm (h) x 57mm (d)			
When ordering please specify the required voltage (ie. NC6-0610-240V)				



NC6-0910

## Miniature Thermal Overload (Type: NR2-11,5)

Code	Applicable	Rated Current	
		AC3 380~440VAC	
		Mid Range	Range
NR2-11.5-0.16A	NC6	0.14A	0.1 - 0.16A
NR2-11.5-0.25A		0.21A	0.16 - 0.25A
NR2-11.5-0.4A		0.33A	0.25 - 0.4A
NR2-11.5-0.63A		0.52A	0.4 - 0.63A
NR2-11.5-1A		0.82A	0.63 - 1A
NR2-11.5-1.6A		1.3A	1 - 1.6A
NR2-11.5-2A		1.6A	1.25 - 2A
NR2-11.5-2.5A		2.1A	1.6 - 2.5A
NR2-11.5-4A		3.3A	2.5 - 4A
NR2-11.5-6A		5.0A	4 - 6A
NR2-11.5-8A		6.5A	5 - 8A
NR2-11.5-10A		8.5A	7 - 10A
NR2-11.5		Separate mounting unit for NR2-11.5	



NR2-11,5

## Auxiliary Contacts

Code	Applicable	Type	Auxiliary Contacts
NCF6-02	NC6	Top Mount	2NC
NCF6-20			2NO
NCF6-11			1NO + 1NC
NCF6-04			4NC
NCF6-13			1NO + 3NC
NCF6-22			2NO + 2NC
NCF6-31			3NO + 1NC
NCF6-40			4NO



NCF6-02



NCF6-40