

RTU33



Earth Leakage (Add on unit)

Code	Applicable	Description
RTU23	TS100~TS250	3, 30, 100, 300mA adjustable to 460, 690V
RTU33	TS400~TS630	3, 30, 100, 300mA adjustable to 460, 690V
RTU43	TS800	3, 30, 100, 300mA adjustable to 460, 690V

MOP4



Motor Operator

Code	Applicable	Description
MOP2	TS100~TS250	24VDC, 100 and 230V AC/DC
MOP3	TS400~TS630	24VDC, 110 and 230V AC/DC
MOP4	TS800	24VDC, 110 and 230V AC/DC

ABN103c



Metasol Moulded Case Circuit Breakers

Code	Rated Current	Short Circuit	Dimensions (mm)
ABN53c	15A, 20A, 30A, 40A, 50A	415V=14kA	130H x 75W x 60D
ABN63c	60A	415V=14kA	130H x 75W x 60D
ABN103c	15A, 20A, 30A, 40A, 50A, 60A, 75A, 100A	415V=18kA	155H x 90W x 60D
ABN203c	100A, 125A, 150A, 200A, 225A, 250A	415V=26kA	165H x 105W x 60D
ABN403c	250A, 300A, 350A, 400A	415V=37kA	257H x 140W x 109D
ABN803c	500A, 630A, 700A, 800A	415V=37kA	280H x 210W x 109D
ABS1003b	1000A	415V=37kA	400H x 220W x 105D
ABS1203b	1200A	415V=37kA	400H x 220W x 105D
ABS1203be	1200A	415V=37kA	400H x 220W x 105D