

DIN Rail (Steel or Aluminium)

Code	Length	Colour	Description
DR35S 1M	1m	Yellow passivated	Slotted
DR35S 2M	2m	Yellow passivated	Slotted

For Aluminium Din Rail change "S" to "A" example (DR35A 1M)



DR35A 1M

Acrylic Sleeving

Code	KA Rating	Size	Length	Colour
IS-01B	2,5kV	1mm	100m	Black
IS-01Y	2,5kV	1mm	100m	Yellow
IS-01,5B	2,5kV	1,5mm	100m	Black
IS-01,5Y	2,5kV	1,5mm	100m	Yellow
IS-02B	2,5kV	2mm	100m	Black
IS-02Y	2,5kV	2mm	100m	Yellow
IS-03B	2,5kV	3mm	100m	Black
IS-03Y	2,5kV	3mm	100m	Yellow
IS-04Y	2,5kV	4mm	100m	Yellow
IS-05Y	2,5kV	5mm	100m	Yellow
IS-06Y	2,5kV	6mm	100m	Yellow
IS-08Y	2,5kV	8mm	100m </td <td>Yellow</td>	Yellow
IS-10Y	2,5kV	10mm	50m	Yellow
IS-12Y	2,5kV	12mm	50m	Yellow



T60x60

Slotted trunking

Code	Dimensions
T25X25	25w x 25h x (2m)
T25X30	25w x 30h x (2m)
T25X40	25w x 40h x (2m)
T40X40	40w x 40h x (2m)
T40X60	40w x 60h x (2m)
T45X80	45w x 80h x (2m)
T55X80	55w x 80h x (2m)
T60X40	60w x 40h x (2m)
T60X60	60w x 60h x (2m)
T80X80	80w x 80h x (2m)
T80X100	80w x 100h x (2m)